

Aluminium-Sechskantprofile	
AlCuMgPb DIN 1725 / EN 754 / EN 755-6 gezogen, gepresst Herstellungslängen ca. 3 Meter	
Schlüsselweite mm	Gewicht kg/m
8,00	0,16
10,00	0,25
12,00	0,36
13,00	0,40
14,00	0,48
17,00	0,71
19,00	0,89
22,00	1,20
24,00	1,42
27,00	1,71
30,00	2,22
32,00	2,53
36,00	3,20
41,00	4,15
46,00	5,13
50,00	5,85
60,00	8,72

Aluminium-Sechskantprofile	
AlMgSi 0,5 F 22 EN AW-6060 T6 DIN EN 754 / EN 755 Herstellungslängen ca. 6 Meter	
Abmessungen h x b x s in mm	Gewicht kg/m
15 x 15 x 2,0	0,15
20 x 20 x 2,0	0,20
20 x 20 x 3,0	0,30
25 x 25 x 2,0	0,26
25 x 25 x 3,0	0,38
30 x 30 x 3,0	0,46
35 x 35 x 3,0	0,55
40 x 40 x 3,0	0,64
40 x 40 x 4,0	0,82
50 x 50 x 4,0	1,04
60 x 60 x 4,0	1,25

Aluminium-U-Profile			
AlMgSi 0,5 F22 EN AW-6060 T6 / DIN EN 754 / EN 755 Herstellungslänge ca. 6 Meter			
Abmessungen in mm h x b x h x s	Gewicht kg/m	Abmessungen in mm h x b x h x s	Gewicht kg/m
10 x 10 x 10 x 2,0	0,15	35 x 35 x 35 x 3,0	0,80
15 x 10 x 15 x 2,0	0,20	20 x 40 x 20 x 2,0	0,41
12 x 12 x 12 x 2,0	0,19	20 x 40 x 20 x 2,5	0,50
15 x 15 x 15 x 2,0	0,23	30 x 40 x 30 x 3,0	0,79
10 x 20 x 10 x 2,0	0,19	40 x 40 x 40 x 2,0	0,63
15 x 20 x 15 x 2,0	0,26	40 x 40 x 40 x 2,5	0,78
20 x 20 x 20 x 2,0	0,32	40 x 40 x 40 x 3,0	0,92
25 x 20 x 25 x 2,0	0,36	40 x 40 x 40 x 4,0	1,25
30 x 20 x 30 x 2,0	0,41	30 x 50 x 30 x 2,0	0,58
40 x 20 x 40 x 2,0	0,52	30 x 50 x 30 x 3,0	0,84
40 x 20 x 40 x 2,5	0,52	50 x 50 x 50 x 3,0	1,17
10 x 25 x 10 x 1,5	0,18	50 x 50 x 50 x 4,0	1,54
15 x 25 x 15 x 2,0	0,28	50 x 50 x 50 x 5,0	1,94
20 x 25 x 20 x 2,0	0,33	20 x 60 x 20 x 2,0	0,52
25 x 25 x 25 x 2,0	0,40	25 x 60 x 25 x 2,5	0,71
25 x 25 x 25 x 3,0	0,56	30 x 60 x 30 x 3,0	0,93
10 x 30 x 10 x 2,0	0,26	40 x 60 x 40 x 2,5	0,91
20 x 30 x 20 x 2,0	0,36	40 x 60 x 40 x 4,0	1,48
20 x 30 x 20 x 3,0	0,54	50 x 60 x 50 x 2,0	0,83
30 x 30 x 30 x 2,0	0,49	50 x 60 x 50 x 2,5	1,05
30 x 30 x 30 x 3,0	0,72	60 x 60 x 60 x 4,0	1,86
15 x 35 x 15 x 2,0	0,31	60 x 60 x 60 x 6,0	2,72
20 x 35 x 20 x 2,0	0,39	25 x 65 x 25 x 2,5	0,74
35 x 35 x 35 x 2,0	0,57	55 x 65 x 55 x 2,5	1,14

Abmessungen in mm h x b x h x s	Gewicht kg/m	Abmessungen in mm h x b x h x s	Gewicht kg/m
20 x 70 x 20 x 2,0	0,58	20 x 100 x 20 x 2,0	0,74
35 x 70 x 35 x 3,0	1,13	40 x 100 x 40 x 3,0	1,40
40 x 70 x 40 x 3,0	1,22	50 x 100 x 50 x 3,0	1,57
20 x 80 x 20 x 2,0	0,63	50 x 100 x 50 x 5,0	2,57
30 x 80 x 30 x 3,0	1,08	50 x 100 x 50 x 6,0	3,05
40 x 80 x 40 x 3,0	1,25	50 x 100 x 50 x 10,0	4,86
30 x 86 x 30 x 3,0	1,19	20 x 120 x 20 x 2,5	1,05
40 x 86 x 40 x 3,0	1,30	40 x 120 x 40 x 3,0	1,58
40 x 90 x 40 x 3,0	1,33	40 x 140 x 40 x 3,0	1,73
50 x 90 x 50 x 3,0	1,49	40 x 200 x 40 x 3,0	2,27

Aluminium-Vierkantrohre

AlMgSi 0,5 F 22

EN AW-6060 T6 / DIN EN 754 / EN 755

Herstellungslängen ca. 6 Meter

Abmessungen a x a x s in mm	Gewicht kg/m	Abmessungen a x a x s in mm	Gewicht kg/m
10 x 10 x 1,0	0,10	45 x 45 x 2,0	0,93
10 x 10 x 1,5	0,14	50 x 50 x 2,0	1,04
15 x 15 x 1,5	0,15	50 x 50 x 3,0	1,54
15 x 15 x 2,0	0,30	50 x 50 x 4,0	1,96
20 x 20 x 1,5	0,28	50 x 50 x 5,0	2,43
20 x 20 x 2,0	0,39	60 x 60 x 2,0	1,25
20 x 20 x 3,0	0,55	60 x 60 x 3,0	1,85
25 x 25 x 1,5	0,37	60 x 60 x 4,0	2,42
25 x 25 x 2,0	0,52	70 x 70 x 2,0	1,47
25 x 25 x 3,0	0,72	70 x 70 x 4,0	2,86
30 x 30 x 2,0	0,61	80 x 80 x 2,0	1,69
30 x 30 x 3,0	0,88	80 x 80 x 3,0	2,50
34 x 34 x 3,0	1,01	80 x 80 x 4,0	3,28
35 x 35 x 2,0	0,76	80 x 80 x 5,0	4,05
35 x 35 x 3,0	1,04	100 x 100 x 2,0	2,12
40 x 40 x 2,0	0,82	100 x 100 x 3,0	3,14
40 x 40 x 3,0	1,20	100 x 100 x 4,0	4,15
40 x 40 x 2,5	1,05	120 x 120 x 2,5	6,21
40 x 40 x 4,0	1,56		