

<b>Rolladen-U-Profil</b>	
Abmessung mm	kg/m
12/12,5/2	0,52
12/20/1,5	0,54
15/15/1,5	0,50
15/20/1,5	0,62
20/20/2,0	0,88
20/20/2,5	1,08
25/25/2,0	1,12
25/25/2,5	1,38
25/25/4,0	2,10
28/40/2,75	2,23
30/30/2,0	1,35
30/30/2,5	1,67
30/30/2,8	1,85
33/33/2,75	2,03
33/50/3,75	3,75
36/36/3,0	2,40
40/40/2,0	1,83
40/40/3,0	2,69
40/40/3,5	3,12
50/50/4,0	4,46
60/55/5,0	6,28

<b>Scheuerleisten</b>	
Abmessung mm	kg/m
50 x 70 x 35 x 2,5 x 10	3,00
40 x 50 x 30 x 2,0 x 10	2,83

<b>T-Stahl versetzt-stegig</b>	
Abmessung mm	kg/m
40/30/3/12,5	1,58
50/35/4/12,5	2,55
75/45/5/19,75	4,65

<b>T-Profile breittfüßig</b>	
Abmessung mm	kg/m
40/20/3,0 ( s )	1,35
40/20/4,5 ( r )	2,00
50/25/5,0 ( r )	2,80
60/30/5,5 ( r )	3,64
60/39/4,0 ( s )	3,10
70/35/6,0 ( r )	4,75
80/40/7,0 ( r )	6,21
100/50/8,5 ( r )	9,42
120/60/10 ( r )	13,40

<b>T-Profile scharfkantig gleichschenkelig</b>	
Abmessung mm	kg/m
20/20/3,0s	0,88
25/25/3,0s	1,15
30/30/3,0s	1,34
30/30/4,0s	1,80
35/35/4,5s	2,33
40/40/4,0s	2,39
40/40/5,0s	3,00
50/50/5,0s	3,90

<b>U-Profile</b>	
Abmessung mm	kg/m
20/10/3/2,75	0,8
20/15/2,5	0,9
24/15/2,0	0,79
30/15/3,0	1,28
30/20/4,0	1,95
30/25/4,0	2,27
35/25/4,0	2,43
36/24/3,0	1,85
40/24/3,25	2,08
45/27/3,25	2,38
50/25/3,0	2,22
50/30/3,25	2,65
50/30/4,0	3,21
60/30/3,0	2,72
60/30/4,0	3,55
60/38/4,0	4,05
70/25/3,0	2,69
70/45/4,0	5,5
80/25/3,5	3,4
100/25/3,5	4,05
100/40/4,0	5,32
120/24/4,0	5,06
140/50/4,0	7,28

<b>Trennwandprofil (kaltprofilier)</b>	
in Längen von 6 Meter	
Abmessung mm	kg/m
2583/30 x 30 x 10 x 2	1,53

<b>Winkelrahmenstahl</b>				
in Längen von 6 Meter				
Maße in mm				Gewicht
a	b	c	d	kg/m
41,00	15,00	15,00	8,00	3,39
53,00	16,00	10,00	8,00	4,00