

<b>T-Stahl rundkantig</b>	
nach DIN 1014 S235 JR hochstegig, rundkantig	
Abmessungen mm	kg/m
20 x 20 x 3,0	0,88
25 x 25 x 3,5	1,29
30 x 30 x 4,0	1,77
35 x 35 x 4,5	2,33
40 x 40 x 5,0	2,96
45 x 45 x 5,5	3,67
50 x 50 x 6,0	4,44
60 x 60 x 7,0	6,23
70 x 70 x 8,0	8,32
80 x 80 x 9,0	10,70
90 x 90 x 10,0	13,40
100 x 100 x 11,0	16,40
120 x 120 x 13,0	23,20
140 x 140 x 15,0	31,30

<b>U-Stahl</b>	
nach DIN 1026 S235 JR	
Abmessungen mm	kg/m
30 x 15 x 4,0	1,74
37 x 17,5 x 4	2,20
30 x 33 x 5,0	4,27
40 x 20 x 5,0	2,87
40 x 35 x 5,0	4,87
50 x 25 x 5,0	3,86
50 x 38 x 5,0	5,59
60 x 30 x 6,0	5,07
65 x 42 x 6,0	7,09

<b>Bandstahl in Stäben</b>					
S235 JR nach DIN 1016, schwarz, warmgewalzt					
Abmessung mm	kg/m	Abmessung mm	kg/m	Abmessung mm	kg/m
10 x 2,0	0,16	30 x 2,0	0,47	100 x 3,0	2,35
10 x 3,0	0,24	30 x 3,0	0,71	100 x 4,0	3,14
10 x 4,0	0,31	30 x 4,0	0,94	110 x 3,0	2,59
12 x 2,0	0,19	35 x 3,0	0,82	110 x 4,0	3,45
12 x 3,0	0,28	35 x 4,0	1,10	110 x 5,0	4,32
12 x 4,0	0,38	40 x 2,0	0,63	110 x 6,0	5,82
15 x 2,0	0,23	40 x 3,0	0,94	120 x 3,0	2,82
15 x 3,0	0,35	40 x 4,0	1,26	120 x 4,0	3,76
15 x 4,0	0,47	45 x 3,0	1,06	120 x 5,0	4,71
16 x 2,0	0,25	45 x 4,0	1,41	120 x 6,0	6,02
16 x 3,0	0,37	50 x 3,0	1,18	130 x 3,0	3,06
16 x 4,0	0,50	50 x 4,0	1,57	130 x 4,0	4,08
18 x 3,0	0,43	55 x 3,0	1,30	130 x 5,0	5,10
18 x 4,0	0,57	55 x 4,0	1,73	130 x 6,0	6,41
20 x 1,0	0,16	60 x 2,0	0,94	140 x 3,0	3,28
20 x 2,0	0,31	60 x 3,0	1,41	140 x 4,0	4,40
20 x 3,0	0,47	60 x 4,0	1,88	140 x 5,0	5,50
20 x 4,0	0,63	70 x 3,0	1,65	140 x 6,0	6,67
25 x 1,0	0,20	70 x 4,0	2,20	150 x 3,0	3,53
25 x 2,0	0,39	80 x 3,0	1,88	150 x 4,0	4,71
25 x 3,0	0,59	80 x 4,0	2,51	150 x 5,0	5,87
25 x 4,0	0,79	90 x 3,0	2,12	150 x 6,0	7,02
30 x 1,0	0,24	90 x 4,0	2,82		